

PRODUCTION OF BIODEGRADABLE POLY LACTIC ACID FROM  
PINEAPPLE INDUSTRY WASTEWATER BY *LACTOBACILLUS*  
*CASEI* FERMENTATION

SABER SALEM HASSAN

A thesis submitted in  
fulfilment of the requirement for the award of the degree  
of Master of Science

Faculty of Science Technology and Human Development  
Universiti Tun Hussein Onn Malaysia

AUGUST 2017

## **DEDICATION**

This research from my Professor, Dr Ramli Bin Hitam, My gratitude for his support and guidance throughout the duration of my part one. Thank you for giving me all the guidelines for this thesis. This research would have certainly been much more difficult without your expertise and knowledge on the subject. I am much obliged to you for all your patience, kindness and generosity. May Allah accept all your good deeds and reward you in the afterlife.

Finally, I hope to Allah to accept this work as SADAKAT to him to support him in doomsday.



PTTA UTHM  
PERPUSTAKAAN TUNKU TUN AMINAH

## ACKNOWLEDGEMENTS

First, I would like to thank Allah for His blessings and for helping me to achieve success in every endeavour of my life. Secondly, I am very grateful and would like to take this opportunity to say you very much to my supervisor.

Special thanks go to Dr. Siti Fatimah Zaharah Mohamad Fuzi, for her assistance throughout this research. Her help has made the task a lot easier.

Also, special to Dr. Suzi Salwah Jikan for her guidance and support throughout my work and for being my sponsor during my studies.

I would also like to express my gratitude to my beloved mum, my brothers, sisters, my supervisor, and all my friends.

Last but not least I would like to thank UTHM especially the Department of Technology for giving me the opportunity to study for my master's degree.

Finally, thank you to ORICC for giving me the support in finishing my research.

May Allah SWA bless all of us!



## ABSTRACT

Pineapple processing industry generates large amount of liquid waste, which contains high concentration of biodegradable organic, suspended solid and high biological oxygen demand (BOD), as well as carbohydrates such as glucose and fructose. The by-products effluent can be a substrate for production of value-added products by microbial fermentation such as biomaterial. However, investigation on the bioconversion of pineapple wastewater to value-added products is still lacking. The objective of this study is to produce biodegradable poly lactic acid (PLA) from pineapple industry waste water by *Lactobacillus casei*. The *L. casei* was cultivated with a medium containing extracted glucose for 24 h. The optimisation of cultural conditions (temperature, pH, inoculum size, nitrogen source) for lactic acid (LA) production was carried out. Purification of LA by reverse osmosis was done. After that, synthesis of PLA was achieved by direct polymerization of pure LA under a nitrogen atmosphere at an optimum time and temperature. Finally, the characterization of PLA was conducted by gel permeation chromatography (GPC), Fourier transform infrared spectroscopy (FTIR), thermogravimetric analysis (TGA) and differential scanning calorimetry (DSC). A maximum production of 31.6 g/l LA was obtained at pH 6, 37 °C and 5% (v/v) of inoculum size. Interestingly, the concentration of pure LA was measured up to 54 g/l after purification. The optimum percentage yield of PLA obtained was 10.4% for 160 °C at 12 h and the molecular weight MW was in the range of 1000 Da to 5215 Da. The highly intense band of 2995 was due to CH stretching of the methylene and methyne groups, a range 1716 to 1748 for ester carbonyl group; other significant bands are in region 1118-1360 typical for ester group -CO-O. A clear glass transition ( $T_g$ ) at 45.3 °C was exhibited when heat synthesis at 160 °C. The results obtained confirmed the production of PLA. Hence it can be concluded that pineapple wastewater can be used for PLA production by *L. casei* under optimum conditions.

## ABSTRAK

Industri pemrosesan nanas menjana sejumlah besar sisa cecair, yang mengandungi organik terdegradasi berkepekatan tinggi, pepejal yang terampai dan oksigen permintaan biokimia yang tinggi (BOD), serta karbohidrat seperti glukosa dan fruktosa. Bahan sisa produk sampingan ini boleh menjadi substrat bagi pengeluaran produk nilai tambah secara penapaian mikroorganism seperti biomaterial. Walau bagaimanapun, penyiasatan mengenai penggunaan air sisa nanas untuk pengeluaran produk nilai tambah adalah terhad. Objektif kajian ini adalah untuk menghasilkan poli LA (PLA) terdegradasi dari air sisa industri nanas oleh *Lactobacillus casei*. *L. casei* telah dibiak dengan medium yang mengandungi glukosa terekstrak selama 24 jam. Pengoptimuman keadaan kultur (suhu, pH, saiz inokulum, sumber nitrogen) untuk pengeluaran asid laktik (LA) telah dijalankan. Penulenan LA oleh osmosis berbalik telah dilakukan. Selepas itu, sintesis PLA diperolehi melalui pempolimeran secara langsung LA tulen di bawah keadaan nitrogen pada masa dan suhu yang optimum. Akhirnya, pencirian PLA dilakukan oleh kromatografi penyerapan gel (GPC), spektroskopi Fourier transform inframerah (FTIR), analisis termogravimetrik (TGA) dan 'differential scanning' kalorimetri (DSC). Pengeluaran maksimum 31.6 g / l LA diperolehi pada pH 6, 37 °C dan 5% (v / v) saiz inokulum. Menariknya, kepekatan LA tulen diukur sehingga 54 g/l selepas penulenan. Hasil peratusan optimum PLA yang diperolehi adalah 10.4 % untuk 160 °C pada 12 jam dan berat molekul MW adalah dalam lingkungan 1000 Da hingga 5215 Da. Jalur yang terlalu kuat pada 2995 disebabkan oleh peregangan CH metilena dan metena, dalam lingkungan 1716 hingga 1748 untuk kumpulan karboksil ester; jalur lain yang penting adalah di kawasan 1118-1360 yang tipikal untuk kumpulan ester -CO-O. Peralihan kaca yang jelas (T<sub>g</sub>) pada 45.3 °C dipamerkan apabila sintesis haba pada 160 °C. Oleh itu, dapat disimpulkan bahawa air kumbahan nanas boleh digunakan untuk pengeluaran PLA oleh *L. casei* di bawah keadaan optimum.

## TABLE OF CONTENTS

<b>TITLE</b>	<b>i</b>
<b>DECLARATION</b>	<b>ii</b>
<b>DEDICATION</b>	<b>iii</b>
<b>ACKNOWLEDGEMENTS</b>	<b>iv</b>
<b>ABSTRACT</b>	<b>v</b>
<b>ABSTRAK</b>	<b>vi</b>
<b>TABLE OF CONTENTS</b>	<b>vii</b>
<b>LIST OF TABLES</b>	<b>xii</b>
<b>LIST OF FIGURES</b>	<b>xiii</b>
<b>LIST OF SYMBOLS</b>	<b>xv</b>
<b>LIST OF ABBREVIATIONS</b>	<b>xvi</b>
<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1 Background	1
1.2 Problem Statement	4
1.3 Objectives	5
1.4 Scope of Study	5
1.5 Significance of the Study	5
1.6 Outline of the Thesis	6
<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>7</b>
2.1 Pineapple Industry	7
2.1.1 Historical Aspects	7
2.1.2 Wide World Production of Pineapple	8
2.1.3 Pineapple Industry in Malaysia	10
2.1.4 Nutrients and Phytochemicals in Pineapple Fruit	10
2.2 Pineapple Waste	13

2.2.1 Pineapple Canning Industry	13
2.2.2 Pineapple Waste Characteristics	14
2.2.3 Pineapple Waste Utilization	15
2.3 LA Industry	16
2.3.1 Historical View Point	16
2.3.2 Physical and Chemical Properties of LA	18
2.3.3 Application of LA	19
2.3.4 Production of LA	19
2.4 Production of LA through Fermentation of Pineapple Wastewater	20
2.5 Fermentation Operating Conditions and Parameters	21
2.5.1 Microorganism for the LA Production	22
2.5.2 Carbon Source	23
2.5.3 Nitrogen Source	24
2.5.4 Temperature	24
2.5.5 pH	25
2.6 Extraction of Fermentation	26
2.7 Purification Techniques of LA	26
2.8 PolyLA (PLA)	28
2.8.1 Background of PLA	29
2.8.2 Synthesis of PLA	30
2.8.3 Direct Polymerization	33
2.8.4 Ring-Opening Polymerization (ROP)	34
2.8.5 Physical and Chemical Properties of Polylactic Acid	35
2.8.6 Advantages of PLA	37
2.8.7 Application and Uses of PLA	37
2.9 Analysis and Characterization of PLA	38
2.9.1 Gel Permeation Chromatography (GPC)	38
2.9.2 Fourier Transform Infrared Spectroscopy (FTIR)	39
2.9.3 Thermo Gravimetric Analysis (TGA)	40
2.9.4 Differential Scanning Calorimetry (DSC)	41



CHAPTER 3 METHODOLOGY	43
3.1 Introduction	43
3.2 Materials	45
3.2.1 Chemical Reagents	45
3.2.2 Microorganism	45
3.2.3 Culture Medium	45
3.2.4 Pineapple Wastewater Liquid	46
3.3.1 Pineapple Wastewater Treatment	46
3.3.2 Extraction of Soluble Sugar	47
3.3.3 Inoculum Preparation	47
3.3.4.1 Cultivation of <i>L. casei</i> in Different Concentration of Carbon Sources	47
3.3.4.2 Effect of pH	48
3.3.4.3 Effect of Temperature	48
3.3.4.4 Effect of Inoculum Size	48
3.3.4.5 Effect of Yeast Extract Concentration	48
3.3.4.6 Growth Profile	48
3.3.5 Optimization and Recovery of LA from Optimum Condition of Fermentation	49
3.3.5.1 Analysis of Lactic acid	50
3.4 Analytical Methods for Characterization of Physical and Chemical Properties	51
3.4.1 Pineapple Wastewater Characterization	51
3.4.1.1 Cation Content	51
3.4.1.2 Anion content	51
3.4.1.3 Bio-Chemical Oxygen Demand (BOD) Content	52
3.4.1.4 Chemical Oxygen Demand (COD)	52
3.4.1.5 Total Sugar Content	52
3.4.1.6 Soluble Sugar in Treated Pineapple Waste	53



3.4.1.7 Soluble Protein Analysis	53
3.4.2.1 Polycondensation Process	54
3.4.2.2 Percentage yield of PLA	55
3.4.2.3 Gel permeation Chromatography (GPC)	55
3.4.2.4 Fourier Transform Infrared (FTIR)	
Spectrophotometer	56
3.4.2.5 Thermo Gravimetric Analysis (TGA)	56
3.4.2.6 Differential Scanning Calorimetric (DSC)	56
3.4.2.7 Statistics Analysis	57

## **CHAPTER 4 RESULTS AND DISCUSSION** **58**

4.1 Introduction	58
4.1.1 Characterization of Pineapple Liquid Waste	58
4.1.2 Soluble Protein Analysis	61
4.1.3 The Measurement of Sugar Contents Before and After Extraction	61
4.2 Fermentation Process for LA Production	63
4.2.1 Investigation of Single Colony Activity	63
4.2.2 Parametric Study of LA Fermentation	64
4.2.2.1 Effect of Different Concentrations of Glucose on Growth of LA producing <i>L. casei</i>	64
4.2.2.2 Influence of Yeast Extract Concentration	65
4.2.2.3 Effect of Various Temperatures on LA Production	66
4.2.2.4 Effect of Various pH on LA Production	67
4.2.2.5 Effect of Inoculum Size	68
4.2.2.6 Influence of Various Carbon Sources on LA Production	70
4.2.3 Fermentation Studies to Optimise the Production of LA from Pineapple waste using <i>L. casei</i> .	71

4.2.4 Extraction and Purification of LA from Optimized Medium of Fermentation Broth	72
4.2.5 Recovery of LA from Fermentation Broth Using Reverse Osmosis Technique	73
4.3 Polycondensation of Lactic Acid	75
4.3.1 Controlling Molecular Weight Analysis	76
4.3.2 Structural Analysis	78
4.3.2.1 Fourier Transform Infrared Spectroscopy (FTIR)	78
4.3.2.2 Thermogravimetric Analysis (TGA)	81
4.3.2.3 Differential Scanning Calorimetry (DSC)	83
<b>CHAPTER 5 CONCLUSION AND RECOMMENDATIONS</b>	<b>87</b>
5.0 Conclusion	87
5.1 Recommendations	88
<b>REFERENCES</b>	<b>89</b>
<b>APPENDICES</b>	<b>103</b>



## LIST OF TABLES

Table 2.1: Export of fresh pineapple as a percentage share of countries' total production	9
Table 2.2: Chemical composition of the edible portion of pineapple	12
Table 2.3: The characteristics of liquid pineapple waste	14
Table 2.4: Physical and Chemical Properties of LA	18
Table 2.5: Microorganisms used for investigations of the biotechnological Production of LA	23
Table 2.6: The comparative of some technology that was used in purification of LA from fermentation broth	28
Table 2.7: Chemical and physical Properties of PLA	36
Table 3.1: Culture media of MRS medium (g/l)	45
Table 3.2: Fermentation media used for LA production	46
Table 3.3: Characteristics of the membrane used.	50
Table 4.1: Comparison of physical and chemical properties of pineapple wastewater samples at different sampling times	59
Table 4.2: The comparative of soluble protein and nitrogen of pineapple wastewater samples at different sampling times	61
Table 4.3: A comparative concentration of sugar content before and after extraction	62
Table 4.4: Concentration of LA fermentation, LA broth and after RO recovery of LA	74
Table 4.5: Molecular weight of samples at different polymerization temperature and time	77
Table 4.6: Thermal properties ( $T_g$ , $T_c$ and $T_m$ ) of PLA synthesised at different temperature and different time determined from DSC thermograms	85

## LIST OF FIGURES

Figure 2. 1: World pineapple production	8
Figure 2. 2: Pineapple canning process	14
Figure 2. 3: Pineapple waste utilisation	16
Figure 2. 4: Enantiomers of lactic acid; D(-)LA and L(+) LA	17
Figure 2. 5: Overview of the two manufacturing methods of lactic acid; (a) chemical synthesis and (b) microbial fermentation	20
Figure 2. 6: Reaction scheme for LA production from carbohydrate	21
Figure 2. 7: Schematic demonstration of reverse osmosis	27
Figure 2. 8: Cycle of PLA in nature	31
Figure 2. 9: Chemical structure of PLA	32
Figure 2. 10: Synthesis of PLA from LA different method of LA polymerization	33
Figure 2.11: Direct polymerization	34
Figure 2. 12: Reaction Scheme of Ring-opening polymerization	35
Figure 3.1: Flowchart of research.	44
Figure 3.2: Schematic diagram of the RO test unit.	49
Figure 3.3: Instrument of membrane technology for recovery	50
Figure 3.4: The setup of polymerization process	54
Figure 4.1: <i>L. casei</i> grown on MRS medium	63
Figure 4.2: Effects of different glucose concentrations on LA production	64
Figure 4.3: LA yield in different concentration of yeast extract.	65
Figure 4.4: Effect of different temperature on LA concentration	66
Figure 4.5: Effect of different the pH on LA production.	67
Figure 4.6: Effect of inoculum sizes on growth and LA production by bacterial <i>L.casei</i>	69
Figure 4.7: (a): Fermentation broth before centrifugation, (b): LA after extraction	72
Figure 4.8: (a) LA broth (b) purity of LA after recovery process.	73
Figure 4.9: PLA synthesis at different times and temperatures (AI at 160 °C for 12 h, AII at 160 °C for 24 h, and BI 180 °C for 12 h, BII 180 °C for 24 h)	75

Figure 4.10: FTIR result for PLA at 160 °C(AI, AII)	79
Figure 4.11: FTIR result for (BI and BII samples) at 180 °C	80
Figure 4.12: TGA and DTG graphs for PLA at 160 °C	81
Figure 4.13: TGA and DTG graphs for PLA at 180 °C	82
Figure 4.14: DSC thermograph for PLA by 160 °C at 12, 24 h	83
Figure 4.15: DSC thermograph for PLA by 180 °C at 12, 24 h	85



## LIST OF SYMBOLS

$^{\circ}\text{C}$	-	Degree Celsius
%	-	percentage
$T_m$	-	melting temperature
$T_g$	-	glass transition temperature.
$T$	-	Time
$T_c$	-	Melting temperature
$M_w$	-	Molecular weight
$V/V$	-	volume per volume
$\text{g/dm}^{-3}$	-	gram per decimeter cubed
$\text{mg/l}$	-	mil gram per liter
$\text{MPa}$	-	mega pascal
$\text{Da}$	-	Dalton
$\text{g/mol}$	-	gram per mole
$\text{cm}^{-1}$	-	Reciprocal centimeter for wavelength

## LIST OF ABBREVIATIONS

LA	-	Lactic acid
MRS	-	De man rogosa and shapes
<i>et al</i>	-	el alia (and other)
g	-	Gram
L	-	Liter
h	-	Hour
mg	-	milligram
OD	-	optical density
rpm	-	revolution per minute
ATCC	-	American Type Culture Collocation Rocckville, Marryland, USA
HPLC	-	high performance liquid Chromatography
LAB	-	LA bacteria
PLA	-	polylactic acid
<i>L.casei</i>	-	<i>Lactobacillus casei</i>
DSC	-	differential scanning colorimetry
GPC	-	Gel permeation chromatography
FTIR	-	Fourier transform infrared spectroscopy
OH	-	hydroxyl group
C=O	-	carbonyl group
CH	-	alkyl group
C-O	-	epoxy and oxiyane rings
FAO	-	Food and agriculture organization
SD	-	Standard division
SE	-	Standard error

## CHAPTER 1

### INTRODUCTION

#### 1.1 Background

The economic actions of many industries such as chemical, petrochemical, agricultural and food have become sources of concern to the world authorities and non-governmental organisations due to the negative effects of these wastes generated by these industries on the environment. For example, pineapple canning industry is amongst the numerous food industries that generate huge amounts of solid and liquids wastes (Vaidya *et al.*, 2005). pineapple canning industry is known as one of the many food industries producing large quantities of solid and liquid wastes. The wastewater from this industry contains a high concentration of biodegradable organic material and thus has high biological oxygen demand (BOD) and highly acidic conditions (low pH) (Mohd Zain *et al.*, 2010; Abdullah, 2007). Due to the stringent environmental regulations regarding waste disposal, the industry has to provide proper treatment. If these waste discharges to the environment are left untreated, they could cause serious environmental problems such as causing health problems to humans and animals and pollution of the soil (Ren, 2011). The resulting effects of these pollution causes health problems to both humans and animals in the environment. Nevertheless, several economic potentials from using food processing wastes (such as pineapple, orange, mango, apple and so on) are possible, since these wastes act as raw materials in the production of useful and high value-added products. For example, the pineapple wastes are used as microbes feed for biological



treatment of wastewater (Jacobsen *et al.*, 2000). Furthermore, about 30% of wastes is generated during the canning process of pineapple (Sairi *et al.*, 2004). The wastes are produced from various sources during production period has varying characteristics and quantities. The cleaning, separation and pineapple concentrate production are the main sources of liquid waste. The liquid waste of the pineapple industry contains 87% of water, 10% of carbohydrate, 1.7% of fiber, 0.7% of protein, 0.5% of ash, and 0.02% of fat (Sutanto, 2012). In general, the food processing industries contribute about 45% of the total organic pollution from agro-based industries. Therefore, this could be used as inexpensive carbon sources for microbial consortium in the production of lactic acid, acetic acid and vinegar (Jin *et al.*, 2005).

LA is an organic compound that is commonly used in the food industry and as substrate for chemical synthesis (Ghaffar *et al.*, 2014). It has been revealed that LA can be utilized as organic material for the production of biodegradable polymers; used for packaging in food industries, medical and pharmaceutical products (Wee *et al.*, 2006; Busairi, 2010). The growth would come from the LA consumption in chemical applications. For example, the use of poly LA and ethyl lactate is expected to expand 19% per year (Subramanian *et al.*, 2015). Currently, the demand of LA was estimated at around 150 million pounds and annual production is between 300,000 to 400,000 tonnes per year (Araya-Cloutier *et al.*, 2012).

LA is produced either through chemical synthesis or microbial fermentation. The chemical synthesis produced racemic dextro (-), levo (+), or mixture (DL) of LA as mentioned by Tront *et al.*, (2011). Alternatively, LA can be produced through fermentation using specific microbial strain. The most commonly used substrate for submerged LA fermentation is refined sugars, which remained costly (Pal *et al.*, 2009). Hence, LA can be produced using cheap substrates (e.g. starch) through two-steps; condition and *Lactobacillus* fermentation processes (Altaf *et al.*, 2007). LA is one of the most widely used organic acids in the food industry and is a very common substrate for chemical synthesis. Currently, LA was found to be the most appropriate feedstock monomer for chemical conversion precisely into valuable chemicals such as biodegradable and biocompatible thermoplastics (e.g. polylactic acid). The PLA is one of the thermoplastic aliphatic polyester LA produced using microbial fermentation of renewable agricultural by-products such as food wastes and starch (Södergård *et al.*, 2002). The PLA found its application mostly in biomedical fields

due to its bioabsorbable properties. However, the recent demand of new polymerization pathways that could permit the economical production of low and high molecular weight PLA, together with the increased in environmental concern of the general public have mandated the widespread application of PLA for goods and packaging purposes (Zhang & Wang, 2008). The biodegradability and sustainable source of PLA make it favorable in reducing the solid waste disposal problems associated with polymeric materials found in the environment. Similarly, its low toxicity and ecofriendly properties made it amongst the most promising material for food packaging and other consumer products (Ren 2009). Therefore, the blending of starch into PLA remained the most encouraging methods for PLA production that could lower the production cost (Zhang *et al.*, 2013). However, the main pathway for beginning LA production involved the instantaneous poly condensation reaction (or ring-opening polymerization) of the lactide monomer.

Additionally, polyLA is widely applied as biodegradable and biomedical materials is because of its outstanding properties that include high mechanical strength, transparency, safety and adaptable to hydrolysis. Also, it has good compatibility and usually toxic free. Thus, it can be degradable in human body, which make it suitable for surgical operations (such as implant material) for temporarily healing process (Lan *et al.*, 2008).

Currently, there is a need for PLA to possess good mechanical properties and stabilities in order to avoid degradation and loss of its high molecular weight during application in packaging, textile and other plastic materials (Zhang and Wang, 2008). However, its application in the biomedical field (such as joint, drug delivery, systems, and dialysis media) required that the material to be easily biodegradable into LA and subsequently metabolize in the body. It may also have some agricultural application. The environmental degradation caused by the disposal of non-biodegradable plastics will be solved if the uses of these polymers are replaced by PLA. In this study, production of biodegradable PLA from pineapple industry waste water by *Lactobacillus casei* was performed. Characterization of PLA using GPC, FTIR, TGA and DSC were performed. Therefore, this research the production of biodegradable poly lactic acid (PLA) from pineapple industry waste water by *Lactobacillus casei*.

## 1.2 Problem Statement

Pineapple processing industries are mostly located in tropical region of the world (such as Malaysia, Thailand, Indonesia) and these factories generate large amount of solid and liquid wastes, and with that waste is contain high concentration of biodegradable organic and suspended solid and also high biological oxygen demand (BOD), and contain mainly carbohydrates such as glucose and fructose.

A high level of BOD and COD in pineapple wastes add to further difficulties in disposal (Agus Sutanto, 2012), these wastes are usually prone to microbial spoilage thus limiting further exploitation. Further, the drying, storage and shipment of these wastes is not cost effective and hence efficient, inexpensive and eco-friendly utilization is becoming more and more necessary. The pineapple wastewater residues may cause serious environmental problems, since it accumulates in agro-industrial yards without having any significant and commercial value (Upadhyay *et al.*, 2013).

However, if the waste can be transformed into useful products such as organic acid by microbial fermentation, then development of biodegradable and bio-based products that are ecologically and economically sustainable can be attained.

The plastics made using conventional raw materials (e.g. petroleum) takes longer time to degrade into harmless substances compared to those produced from renewable organic materials. Besides, worldwide concern on disposal of plastic wastes produced from petrochemical-based materials have not been relented due to its environmental impact. Consequently, biodegradable materials, e.g. PLA, have been thoroughly studied in order to substitute the current petro-based polymers. The polymer from renewable sources has several benefits over other polymers; significant energy reduction during production and ability to recycle back to non-toxic, naturally occurring LA through either hydrolysis or alcoholysis. The PLA is primarily obtained from ecofriendly sources which degrade quickly into the environment with virtually very low toxicity. The study on biodegradable polymers recently has gained significant momentum due to its utmost desirability and ecofriendly. However, investigation on the utilisation of pineapple wastewater for production of PLA is scarce. Thus, if wastewater from pineapple can be converted into products such as organic acids; this would derive more value to the waste and in the long run, provide a solution to the environmental problems.

### 1.3 Objectives

The objectives of the present research are:

- i. To characterise the quality of pineapple wastewater.
- ii. To extract sugars from pineapple waste.
- iii. To produce lactic acid using pineapple wastewater extracted sugar by *L.casei* fermentation.
- iv. To isolate lactic acid from the fermented broth.
- v. To synthesise poly (lactic acid) polymer by condensation polymerization technique.

### 1.4 Scope of Study

- i. Characterization of physical and chemical properties of pineapple wastewater.
- ii. Extraction of sugar content from pineapple wastewater by using rotary evaporator system.
- iii. Optimisation of cultural conditions (such as pH, temperature, inoculum size) for high level production of LA.
- iv. Purification of LA from the fermentation broth by using reverse osmosis technology.
- v. Direct polycondensation of LA for synthesizing PLA under nitrogen condition at different temperature and time.
- vi. Characterization of PLA using gel permeation chromatography (GPC), Fourier Transform Infrared spectrophotometer (FTIR), differential scanning calorimetry (DSC) and thermogravimetric analysis (TGA).

### 1.5 Significance of the Study

This study was carried out to:

- i. Obtain a high LA yield from the pineapple waste.

- ii. Provide a low-cost carbon source for bacterial growth.
- iii. Propose a biodegradable substitute for petroleum-based plastic, from unusable pineapple waste material.

## **1.6 Outline of the Thesis**

The thesis is basically divided into five chapters. The research background, research objective and scope of the study are outlined in Chapter 1. An extensive literature review had been carried out prior to the experimental work. A literature review was conducted to provide background to the research project and this is discussed in detail in Chapter 2.

Chapter 3 provides a methodology which includes the steps of the extraction of the carbohydrate, production of LA and the synthesis of PLA. Characterization and recovery of the glucose and optimisation of carbon sources, steps of the fermentation process, and optimisation of pH and temperature as well as polymerization process and the characterization of the synthesised PLA are also discussed.

Chapter 4 consists of a discussion of the results obtained from all the tests conducted including the quality of pineapple wastewater and the whole steps for fermentation process and optimisation of the cultural condition in order to obtain maximum LA. Polymerization steps were performed to produce PLA and characterizations of PLA were determined. Finally, Chapter 5 consists of conclusion and recommendation for future studies.

## CHAPTER 2

### LITERATURE REVIEW

#### 2.1 Pineapple Industry

##### 2.1.1 Historical Aspects

Pineapple (*Ananas comosus*) is usually a tropical crop grown mostly in Brazil, and other tropical countries of the world. In 1914, the Pineapple Growers Association of Hawaii launched one of the earliest and best rigorous efforts in pineapple improvement. Their major goal was to develop pest and disease resistance species of pineapple. This led to the development of other agricultural groups in numerous countries (for instance, in Taiwan, Malaysia, Philippines, Cote D'Ivoire, Puerto Rico, Cuba and Australia) to begin hybridization programs for high yield varieties that can adjust to their specific environmental conditions (Guillermo *et al.*, 2011; Shari *et al.*, 2004). The fruit was introduced to Malaysia by Portuguese in the 16<sup>th</sup> century and initially planted in Johor and Selangor as a cash crop. After some time, the plantation of the fruit was later extended to the peat soil area, particularly in Johor (Hajar *et al.*, 2012).

Currently, the world major producers of pineapple include Malaysia, Thailand, Philippines, Indonesia, Hawaii, Ivory Coast, Kenya, Brazil, Taiwan, Australia, India and South Africa. Similarly, countries like Japan, United States of America (USA), European Economic Union (EEU) West Asia and Singapore have high market demand of canned pineapple fruit (<http://mpib.gov.my/en/sejarah>).



### 2.1.2 Wide World Production of Pineapple

Pineapple has long remained one of the most prevalent among the non-citrus tropical and subtropical fruits, due to its attractive taste and stimulating sugar-acid stability (Sairi *et al.*, 2004). The global production started as early as 1500 when it was spread in Europe and other tropical regions of the world. The most spread specie is *Cayenalis* variety of pineapple (Smooth Cayenne) which was originated from French Guyana and introduced to Europe. The first canned pineapple was introduced commercially in the late 19th century in Hawaii (Garcia *et al.*, 2005).

Pineapple is a member of the Bromeliaceae family (monocotyledons) and consist of about 2000 species with an yearly global production of over 14 million tonnes; it is the eighth most plentifully fruit in the world (Hajar *et al.*, 2012). This pommel fruit was perhaps indigenous to Brazil, and it had spread to other parts of tropical America by the time of Columbus who took it to Europe. Currently, the fruit was found to grow all over the tropical and subtropical regions of the world as shown in Figure 2.1.(Dhar *et al.*, 2008).




Figure 2.1: World pineapple production (Dhar *et al.*, 2008).

The world production of pineapple fruit was 21,865,383 tonnes in 2011 and China (the world highest pineapple producer) accounted for about 6.2% (1,351,367 metric tonnes) of the total world's pineapple production (Lu *et al.*, 2014). However, a recent study shows that the global pineapple industry is controlled by countries like Costa Rica and the Philippines while countries like Belgium and the Netherlands are the major re-exporter of the product. Belgium, France and Germany, Netherlands participate in the world trade by re-exporting the product. Apart from the Philippines, the six chief pineapple producers in the world contribute insignificant quantities to the market of fresh pineapple trade (Table 2.1), (FAO. 2009). The largest exporter of fresh pineapple is Costa Rica (54%), followed by Belgium (10%), Philippines (7%), Netherlands (7%), Ecuador (4%) and the US (3%). The annual export growth recorded between 2005 and 2009 is 30% and 35% of production volume 2.15 to 2.8 million metric tonnes and values \$1.1 to \$1.5 billion, respectively (Survey, 2012).

Regardless of the rapid growth of the fresh pineapple, the pineapple growing is extremely profitable and have great significance by generating employment and income, and thus, it is broadly exploited throughout the tropical regions and needs serious hand-farming by a countryside man power (Amorim *et al.*, 2013).

Table 2.1: Export of fresh pineapple as a percentage share of countries' total production (Amorim *et al.*, 2013).

Country	Percentage
Netherlands	88.9
Ivory Coast	82.2
Belgium	78.9
Costa Rica	67.9
Honduras	61.3
France	52.2
Ghana	36.4
Malaysia	14.7
Nicaragua	12.9
United State	12.5
Germany	11.2
Philippines	8.9
Ecuador	5.1
México	4.7
Brazil	1.2
Thailand	0.2
China	0.2
India	0.1



## REFERENCES

- Abdullah, A. (2007). Solid and Liquid Pineapple Waste Utilization for Lactic acid Fermentation using *Lactobacillus delbrueckii*. *Reaktor*, 11(1), 50-52.
- Abdullah, A., & Mat, H. (2008). Characterisation of Solid and Liquid Pineapple Waste. *Reaktor*, 12(1), 48-52.
- Ahmed, J., & Varshney, S. K. (2011). Polylactides—Chemistry, Properties and Green Packaging Technology: A review. *International Journal of food Properties*, 14(1), 37-58.
- Aljundi, I. H., Belovich, J. M., & Talu, O. (2005). Adsorption of Lactic acid from Fermentation Broth and Aqueous Solutions on Zeolite Molecular Sieves. *Chemical Engineering Science*, 60(18), 5004-5009.
- Altaf, M., Naveena, B., & Reddy, G. (2007). Use of Inexpensive Nitrogen Sources and Starch for L (+) lactic acid Production in Anaerobic Submerged Fermentation. *Bioresource Technology*, 98(3), 498-503.
- Amorim, A. V., Garruti, D. d. S., Lacerda, C. F. d., Moura, C. F. H., & Gomes-Filho, E. (2013). Postharvest and Sensory Quality of Pineapples Grown Under Micronutrients Doses and Two Types of Mulching. *African Journal of Agricultural Research, Lagos*, 8(19), 2240-2248.
- Araya-Cloutier, C., Rojas-Garbanzo, C., & Velázquez-Carrillo, C. (2012). Effect of Initial Sugar Concentration on the Production of L (+) lactic acid by Simultaneous Enzymatic Hydrolysis and Fermentation of an Agro-industrial Waste Product of Pineapple (*Ananas comosus*) using *Lactobacillus casei* Subspecies Rhamnosus. *International Journal of Biotechnology for Wellness Industries*, 1(1), 91-100.
- A.R. Berry, C.M.M. Franco, W. Zhang, A.P.J. Middelberg, (1999). Growth and lactic acid production in batch culture of *Lactobacillus rhamnosus* in a defined medium, *Biotechnol. Lett.* 21 (1999) 163–167.

- Assous, M., Saad, E. S., & Dyab, A. (2014). Enhancement of Quality Attributes of Canned Pumpkin and Pineapple. *Annals of Agricultural Sciences*, 59(1), 9-15.
- Augstburger, F., et al. "Organic Farming in the Tropics and Sub Tropics: Exemplary Description of Pineapples." *Grafelfing, Germany* (2001): 333- 342.
- Auras, R. A., Lim, L.-T., Selke, S. E., & Tsuji, H. (2011). Poly (lactic acid): Synthesis, Structures, Properties, Processing, and Applications (Vol. 10): *John Wiley& Sons*.
- Av érous, L. (2008). *Polylactic acid: Synthesis, Properties and Applications* (pp. 433-450). Elsevier: Oxford, UK.
- A.W. Schepers, J. Thibault, C. Lacroix,(2002). Lactobacillus helveticus growth and lactic acid production during pH- controlled batch cultures in whey Microb. permeate / yeast extract medium. Part I. Multiple factor kinetic analysis, *Enzyme Technol.* 30 (2002) 176–186.
- Banik, S., Nag, D., & Debnath, S. (2011). Utilization of Pineapple Leaf Agro-waste for Extraction of Fibre and the Residual Biomass for Vermicomposting. *Indian Journal of Fibre and Textile Research*, 36(2), 172-177.
- Belgacem, Mohamed Naceur,Alessandro Gandini. (2008). Materials from Vegetable Oils: major sources, properties and applications. *Monomers, Polymers and Composites from Renewable Resources*, 39-66.
- Buruleanu, Lavinia Claudia, et al. (2013). *Fermentation of Vegetable Juices by Lactobacillus Acidophilus LA-5*: Intech Open Access Publisher.
- Busairi, A. M. (2010). Effect of Nitrogen Source and Initial Sugar Concentration on Lactic acid Fermentation of Pineapple Waste using *L. delbrueckii*. *Teknik*, 31(1), 31-34.
- Cánara, M., Diez, C., & Torija, E. (1995). Chemical Characterization of Pineapple Juices and Nectars. Principal Components Analysis. *Food Chemistry*, 54(1), 93-100.
- Cartier, L., Okihara, T., Ikada, Y., Tsuji, H., Puiggali, J., & Lotz, B. (2000). Epitaxial Crystallization and Crystalline Polymorphism of Polylactides. *Polymer*, 41(25), 8909-8919.

- Carné Sánchez, A. and Collinson, S.R. The Selective Recycling of Mixed Plastic Waste of Polylactic acid and Polyethylene Terephthalate by Control of Process Conditions. *European Polymer Journal*. 2011. 47(10): 1970-1976.
- Cao, X., Mohamed, A., Gordon, S. H., Willett, J. L., & Sessa, D. J. (2003). DSC study of biodegradable poly (lactic acid) and poly (hydroxy ester ether) blends. *Thermochimica acta*, 406(1), 115-127.
- Chandrabu, S., Mythily, R., & Kumar, C. C. (2011). Liquid - Liquid Extraction of Sugars from non Edible Pineapple (*Ananas comosus*) and Analysis by sophisticated liquid chromatography / Mass Spectroscopy and Thin Layer Chromatographic Analysis. *International Journal of Current Scientific Research*, 1(3), 125-128.
- Chenguang, Jia, Y., & He, A. (2013). "Preparation of Higher Molecular Weight Poly (L-lactic acid) by Chain Extension." *International Journal of Polymer Science* 2013, 1–7.
- Chieng, B. W., Ibrahim, N. A., Yunus, W. M. Z. W., & Hussein, M. Z. (2013). Poly (lactic acid)/Poly (Ethylene glycol) Polymer Nanocomposites: Effects of Graphene Nanoplatelets. *Polymers*, 6(1), 93-104.
- Choi, H.-Y., Ryu, H.-K., Park, K.-M., Lee, E. G., Lee, H., Kim, S.-W., & Choi, E.-S. (2012). Direct lactic acid Fermentation of Jerusalem Artichoke Tuber Extract using *Lactobacillus paracasei* without acidic or Enzymatic Inulin Hydrolysis. *Bioresource Technology*, 114, 745-747.
- Cordenunsi, B., Saura-Calixto, F., Diaz-Rubio, M. E., Zuleta, A., Tiné M. A., Buckeridge, M. S., . . . Lajolo, F. (2010). Carbohydrate Composition of Ripe Pineapple (cv. perola) and the Glycemic Response in Humans. *Food Science and Technology* (Campinas), 30(1), 282-288.
- Costa, M. G. M., Fonteles, T. V., de Jesus, A. L. T., & Rodrigues, S. (2013). Sonicated Pineapple Juice as Substrate for *L. casei* Cultivation for Probiotic Beverage Development: Process Optimisation and Product Stability. *Food Chemistry*, 139(1-4), 261-266.
- C.N. Burgos-Rubio, M.R. Okos, P.C. Wankat, (2000). Kinetic study of the conversion of different substrates to lactic acid using *Lactobacillus bulgaricus*, *Biotechnol. Progr.* 16 (2000) 305– 314.
- C. Vishnu, G. Seenayya, G. Reddy, (2000). Direct conversion of starch to L(+)-lactic

- acid amylase producing *Lactobacillus amylophilus* GV6, *Bioprocess Eng.* 23 (2000) 155–158.
- C. Kotzanmanidis, T. Roukas, G. Skaracis, (2002). Optimization of lactic acid production from beet molasses *Lactobacillus delbrueckii* NCIMB 8130, *World J. Microbiol. Biotechnol.* 18 (2002) 442–448.
- Dacera, D. D. M., Babel, S., & Parkpian, P. (2009). Potential for Land Application of Contaminated Sewage Sludge Treated with Fermented Liquid from Pineapple Wastes. *Journal of Hazardous Materials*, 167(1-3), 866-872.
- De Geyter, N. (2013). Influence of Dielectric Barrier Discharge Atmosphere on polylactic acid (PLA) Surface Modification. *Surface and Coatings Technology*, 214, 69-76.
- De La Cruz, J., & Garcia, G. H. (2004). *Pineapple: Post-harvest operations*. FAO document for Internet site: [www.fao.org/inpho/compendium](http://www.fao.org/inpho/compendium).
- De La Cruz, J., & Garcia, G. (2005). "Pineapple: Post-harvest operations. Food and Agriculture Organization of the United Nations, pp: 1-38." [www.Fao.org/Inpho/Compendium](http://www.Fao.org/Inpho/Compendium), (2005).
- Dey, P., Linnanen, L., & Pal, P. (2012). Separation of Lactic acid from Fermentation Broth by Cross Flow Nanofiltration: Membrane Characterization and transport Modelling. *Desalination*, 288, 47-57.
- Dhar, M., Rahman, S., & Sayem, S. (2008). Maturity and Post Harvest Study of Pineapple with Quality and Shelf Life Under Red soil. *Int. J. Sustain. Crop Prod*, 3(2), 69-75.
- Diltz, R. A., Marolla, T. V., Henley, M. V., & Li, L. (2007). Reverse Osmosis Processing of Organic Model Compounds and Fermentation Broths. *Bioresource Technology*, 98(3), 686-695.
- Dutkiewicz, S., Grochowska-Łapienis, D., & Tomaszewski, W. (2003). Synthesis of Poly (L (+) lactic acid) by Polycondensation Method in Solution. *Fibres & Textiles in Eastern Europe*, 4(43), 66--70.
- Erickson, L., Fayet, E., Kakumanu, B., & Davis, L. (2004). " *Carcass Disposal: a Comprehensive Review*, National Agricultural Biosecurity Center, Manhattan, Kansas.
- Byrne, F., Ward, P. G., Hughes, D., Cullen, J., & Dowling, D. P. (2007, August). Comparative Study of the Processing Conditions Required for PLA and PET

- Polymers. In *Proceedings of the IMF Conference, Waterford Institute of Technology, Ireland*.
- Farooq, U., Anjum, F. M., Zahoor, T., Rahman, S.-U., Randhawa, M. A., Ahmed, A., & Akram, K. (2012). Optimization of Lactic acid Production from Cheap Raw Material: Sugarcane Molasses. *Pak. J. Bot*, 44(1), 333-338.
- França, F. P., de Jesus, A. M., & Oliveira, F. J. S. (2009). Enhancement of Lactic acid Fermentation by *Lactobacillus delbrueckii* ATCC 6949 using Sugarcane Molasses. *Canadian Journal of Pure and Applied Sciences*, 3(2), 773-778.
- García, J. D. L. C. M. and H. S. (2005). *pineapple: Post-harvest Operations*. Instituto Tecnológico de Vaeracruz.
- Ghaffar, T., Irshad, M., Anwar, Z., Aqil, T., Zulifqar, Z., Tariq, A., Mehmood, S. (2014). Recent Trends in Lactic acid Biotechnology: A brief Review on Production to Purification. *Journal of Radiation Research and Applied Sciences*, 7(2), 222-229.
- Ghasemi, M., Najafpour, G. D., Younesi, H., Rahimnejad, M., & Rezaee, P. S. (2009) Influence of Yeast Extract concentration on Lactic Acid Production from Whey in Batch Reactor by *Lactobacillus bulgaricus*.
- González, M. I., Alvarez, S., Riera, F. A., & Álvarez, R. (2008). Lactic acid Recovery from Whey Ultrafiltrate Fermentation Broths and Artificial Solutions by nanofiltration. *Desalination*, 228(1), 84-96.
- Guillermo, P., Ermis, Y., Andrew, M., Bárbara, V., Fernando, S., Lourdes, Y., Carlos, A., Justo, G., Miriam, I., and José Carlos, L. New Pineapple Somaclonal Variants: P3R5 and Dwarf. *American Journal of Plant Sciences*. 2011. 2012.
- Gunatillake, P. A., & Adhikari, R. (2003). Biodegradable Synthetic Polymers for Tissue Engineering. *European Cell Materials*, 5(1), 1-16.
- G. Bustos, A.B. Moldes, J.M. Cruz, J.M. Domínguez, (2004). Production of fermentable media from vine-trimming wastes and bioconversion into lactic acid by *Lactobacillus pentosus*, *J. Sci. Food Agric*. 84 (2004) 2105–2112.
- Hajar, N., Zainal, S., Nadzirah, K., Roha, A. S., Atikah, O., & Elida, T. T. (2012). Physicochemical Properties Analysis of Three Indexes Pineapple (*Ananas Comosus*) Peel Extract Variety N36. *Apchec Procedia*, 4, 115-121.
- Hemalatha, R., & Anbuselvi, S. (2013). Physicochemical Constituents of Pineapple Pulp and Waste. *Journal of Chemical & Pharmaceutical Research*, 5(2).

- Henton, David. E., Gruber, P., Lunt, J., & Randall, J. (2005). Polylactic Acid Technology. *NaturalFibers, Biopolymers, and Biocomposites*, 16, 527-577.
- Huang, L. P., Jin, B., Lant, P., & Zhou, J. (2005). Simultaneous Saccharification and Fermentation of Potato Starch Wastewater to Lactic acid by *Rhizopus Oryzae* and *Rhizopus Arrhizus*. *Biochemical Engineering Journal*, 23(3), 265-276.
- Hujanen, M., Linko, S., Linko, Y.-Y., & Leisola, M. (2001). Optimisation of Media and Cultivation Conditions for L (+)(S)-Lactic acid Production by *Lactobacillus casei* NRRL B-441. *Applied Microbiology and Biotechnology*, 56(1-2), 126-130.
- Hu, Y., Daoud, W. A., Cheuk, K. K. L., & Lin, C. S. K. (2016). Newly developed techniques on polycondensation, ring-opening polymerization and polymer modification: focus on poly (lactic acid). *Materials*, 9(3), 133.
- Jacobsen, S., Fritz, H.-G., Degée, P., Dubois, P., & Jérôme, R. (2000). New Developments on the Ring Opening Polymerisation of Polylactide. *Industrial Crops and Products*, 11(2), 265-275.
- Jamshidian, M., Tehrani, E. A., Imran, M., Jacquot, M., & Desobry, S. (2010). Poly-lactic acid: production, applications, nanocomposites, and release studies. *Comprehensive Reviews in Food Science and Food Safety*, 9(5), 552-571.
- Jin, B., Yin, P., Ma, Y., & Zhao, L. (2005). Production of Lactic acid and Fungal Biomass by *Rhizopus Fungi* from Food Processing Waste Streams. *Journal of Industrial Microbiology and Biotechnology*, 32(11-12), 678-686.
- Jusoh, N., Othman, N., Idris, A., & Nasruddin, A. (2014). Characterization of Liquid Pineapple Waste asCarbon Source for Production of Succinic acid. *Jurnal Teknologi*, 69(4).
- Kaitian, X., Kozluca, A., Denkbaz, E. B., & Piskin, E. (1996). Poly (D, L-lactic acid) Homopolymers: Synthesis and Characterization. *Turkish Journal of Chemistry*, 20, 43-53.
- Kim, S., Baek, Y., Oh, S., Sim, J., & Rheem, S. (1995). Optimizing conditions for the Growth of *Lactobacillus casei* YIT 9018in Tryptone-Yeast Extract-Glucose Medium by Using Response Surface Methodology. *Applied and Environmental Microbiology*, 61(11), 3809.



- Kimmel, S. A., Roberts, R. F., & Ziegler, G. R. (1998). Optimization of Exopolysaccharide Production by *Lactobacillus delbrueckii subsp. Bulgaricus* RR Grown in a Semidefined Medium. *Applied and Environmental Microbiology*, 64(2), 659-664.
- Lan, P., & Lv, J. (2008). Study on Synthesis and Mechanism of Melt Polymerization of L-lactic acid. *Journal of Fiber Bioengineering and Informatics*, 1(1), 41-46.
- Lasprilla, A. J. R., Martinez, G. A. R., Lunelli, B. H., Figueroa, J. E. J., Jardini, A. L., & Filho, R. M. (2011). Synthesis and Characterization of Poly (lactic acid) for use in Biomedical Field. *Chemical. Engineering*, 24, 985-990.
- Leao, A. L., Cherian, B. M., Narine, S., Souza, S., Sain, M., & Thomas, S. (2014). The Use of Pineapple Leaf Fibers (PALFs) as Reinforcements in Composites. *Biofiber Reinforcements in Composite Materials*(51), 211.
- Lim, C.H., 1 Rahim, R.A., 2 Ho, Y.W.3 and Arbakariya, B. A. (2007). Optimization of Growth Medium for Efficient Cultivation of *Lactobacillus salivarius* i 24 using Response Surface Method Responses, 3(2), 41–47.
- Lim, L.-T., Auras, R., & Rubino, M. (2008). *Processing Technologies for Poly (lactic acid)*. *Progress in Polymer Science*, 33(8), 820-852.
- Lin, R. M., & Rahman, A. A. (2010). Status and Impact of Pineapple Technology on Mineral Soil. *Economic and Technonlogy Management Review*, Vol,5;11-9
- Lopes, M. S., Jardini, A. L., & Filho, R. M. (2014). Synthesis And Characterizations Of Poly (lactic Acid) By Ring-opening Polymerization For Biomedical Applications. *Chemical Engineering Transactions*. 38, 331–336. doi:10.3303/CET1438056.
- Lu, X.-H., Sun, D.-Q., Wu, Q.-S., Liu, S.-H., & Sun, G.-M. (2014). Physico-chemical properties, antioxidant activity and mineral contents of pineapple genotypes grown in China. *Molecules*, 19(6), 8518-8532.
- Lun, O. K., Wai, T. B., & Ling, L. S. (2014). Pineapple Cannery Waste as a Potential Substrate for Microbial Biotranformation to Produce Vanillic acid and Vanillin. *International Food Research Journal*, 21(3).
- Madaeni, S., & Mansourpanah, Y. (2004). Chemical Cleaning of Reverse Osmosis Membranes Fouled by Whey. *Desalination*, 161(1), 13-24.

- Maizatunisa, Othman, et al. (2013). FTIR and TGA Analysis of Biodegradable Poly (Lactic acid)/Treated Kenaf Bast Fibre: Effect of Plasticizers. " *Pertanika Journal of Science & Technology* 21.1 (2013): 151-160.
- Marek gryta<sup>1\*</sup>, Justyna Bastrzyk<sup>1</sup>, w. t. (2014). The Application of Membrane Processes for Separation of Post-Fermentation Glycerol. *Membranes and Membrans Processes*, 119, 241–250.
- Ma, X., Yu, J., & Wang, N. (2006). Compatibility characterization of poly (lactic acid)/poly (propylene carbonate) blends. *Journal of Polymer Science Part B: Polymer Physics*, 44(1), 94-101.
- Milcent, S. (2001). Clarification of Lactic acid Fermentation Broths. *Separation and Purification Technology*, 22-23(1-2), 393–401.
- Mochamad Busairi, A. (2008). Conversion of Pineapple Juice Waste into Lactic acid in Batch and Fed - Batch Fermentation Systems. *Reaktor*, 12(2), 98-101.
- Mohd Zain, N. A., Mohd Suardi, S., & Idris, A. (2010). Hydrolysis of Liquid Pineapple Waste by Invertase Immobilized in PVA–Alginate Matrix. *Biochemical Engineering Journal*, 50(3), 83–89. doi:10.1016/j.bej.2010.02.009.
- Mojsov, K. (2010). The Effects of Different Carbon Sources on Biosynthesis of Pecinolytic Enzymes by *Aspergillus Niger*. *Applied Technologies & Innovations*, 3(3), 23-29.
- Montaudo, G., Montaudo, M. S., Puglisi, C., & Samperi, F. (1995). Characterization of Polymers by matrix-assisted laser desorption/ionization time-of-flight mass spectrometry: Molecular Weight Estimates in Samples of Varying Polydispersity. *Rapid communications in mass spectrometry*, 9(5), 453-460.
- M. Hujanen, Y.Y. Linko,(1996). Effect of temperature and various nitrogen sources on L (+) - lactic acid production by *Lactobacillus casei*, *Appl. Microbiol. Biotechnol.* 45 (1996) 307–313.
- Nadzirah, K., Zainal, S., Noriham, A., Normah, I., Siti Roha, A., & Nadya, H. (2013). Physico-chemical properties of pineapple variety N36 harvested and Stored at Different Maturity Stages. *International Food Research Journal*, 20(1), 225-231.



- Narayanan, N., Roychoudhury, P. K., & Srivastava, A. (2004). L (+) lactic acid Fermentation and its Product Polymerization. *Electronic Journal of Biotechnology*, 7(2), 167-178.
- Nasir, N. A. M., Kamalbahrin, M. A. M., Mohamad, N. S., Anuar, H., Mel, M., & Othman, R. (2011). Effect of *Rhizopus Oryzae* Fermentation on Kenaf-Based Polylactic acid's Monomer. *IIUM Engineering Journal*, 12(4), 83-87.
- Natthawut Yodsuwan<sup>1</sup>, Amorn Owatworakit<sup>1</sup>, Atitaya Ngaokla<sup>2</sup>, Nattaya Tawichai<sup>1</sup>, A., & Soykeabkaew<sup>1</sup>, N. (2012). Effect of carbon and nitrogen sources on Bacterial Cellulose Production for Bionanocomposite Materials, In *1st Fah Luang University International Conference, Thailand*.
- Ngadi, N., Yusoff, N. H., & Mat Ludin, S. (2005). Production of Lactic acid from Pineapple Wastes in Anaerobic culture. *Kustem 4th Annual Seminar On Sustainability Science And Management, Primula Beach Resort , Kuala Terengganu*.
- N.D. Roble, J.C. Ogbonna, H. Tanaka, (2003). L- lactic acid production from raw cassava starch in a circulating loop bioreactor with cell immobilized in loofa (*Luffa cylindrica*), *Biotechnol.Lett.* 25 (2003) 1093–1098
- Oh, H., Wee, Y.-J., Yun, J.-S., Han, S. H., Jung, S., & Ryu, H.-W. (2005). Lactic acid Production from Agricultural Resources as Cheap Raw Materials. *Bioresource Technology*, 96(13), 1492-1498.
- Oh, S., Rheem, S., Sim, J., Kim, S., Baek, Y., Oh, S., Kim, S. (1995). Optimizing Conditions for the Growth of *Lactobacillus casei* YIT 9018 in Tryptone-Yeast Extract-Glucose Medium by using Response Surface Methodology. *Applied and environmental microbiology*, 61(11), 3809-3814.
- Okun, D. T., Lane, C. R., Williamson, I. A., & Pinkert, D. A. (2007). Canned Pineapple Fruit From Thailand U . S . *International Trade Commission*, 706(731).
- Omay, D., & Guvenilir, Y. (2014). Lactic acid Fermentation from Refectory Waste: Factorial Design Analysis. *African Journal of Biotechnology*, 11(30), 7693-7700.
- Orozco, F., Valadez-González, A., Domínguez-Maldonado, J., Zuluaga, F., Figueroa-Oyosa, L., & Alzate-Gaviria, L. (2014). Lactic acid Yield using

- Different Bacterial Strains, its Purification, and Polymerization Through Ring-Opening Reactions. *International Journal of Polymer Science*, 2014.
- Orozco, F., Valadez-González, A., Domínguez-Maldonado, J., Zuluaga, F., Figueroa-Oyosa, L., & Alzate-Gaviria, L. (2014). Lactic acid Yield using Different Bacterial Strains, its Purification, and Polymerization Through Ring-Opening Reactions. *International Journal of Polymer Science*, 2014.
- Orozco, V. H., Brostow, W., Chonkaew, W., & Lopez, B. L. (2009, February). Preparation and characterization of poly (Lactic acid)-g-maleic anhydride+ starch blends. In *Macromolecular symposia* (Vol. 277, No. 1, pp. 69-80). Wiley-vch verlag.
- Ozaki, H., & Li, H. (2002). Rejection of Organic Compounds by Ultra-low Pressure Reverse Osmosis Membrane. *Water research*, 36(1), 123-130.
- Pal, P., Sikder, J., Roy, S., & Giorno, L. (2009). Process Intensification in Lactic acid Production: A review of Membrane Based Processes. *Chemical Engineering and Processing: Process Intensification*, 48(11-12), 1549-1559.
- Palacio, J., Orozco, V. H., & López, B. L. (2011). Effect of the Molecular Weight on the Physicochemical Properties of Poly (lactic acid) Nanoparticles and on the Amount of Ovalbumin Adsorption. *Journal of the Brazilian Chemical Society*, 22(12), 2304-2311.
- Palles, T., Beresford, T., Condon, S., & Cogan, T. M. (1998). Citrate metabolism in *Lactobacillus casei* and *Lactobacillus plantarum*. *Journal of Applied Microbiology*, 85(1), 147-154.
- Panesar, P. S., Kennedy, J. F., Knill, C. J., & Kosseva, M. (2010). Production of L (+) Lactic acid using *Lactobacillus casei* from Whey. *Brazilian Archives of Biology and Technology*, 53(1), 219-226.
- Pivsa-Art, S., Tong-ngok, T., Junngam, S., Wongpajan, R., & Pivsa-Art, W. (2013). Synthesis of poly (D-Lactic Acid) Using a 2-Steps Direct Polycondensation Process. *Energy Procedia*, 34, 604-609.
- Putri, W. D. R., Marseno, D. W., & Cahyanto, M. N. (2012). Role of lactic acid Bacteria on Structural and Physicochemical Properties of Sour Cassava Starch. *Apchbee Procedia*, 2, 104-109.

- Pyar, H., Liong, M.-T., & Peh, K. (2014). Potentials of Pineapple Waste as Growth Medium for *Lactobacillus species*. *International Journal of Pharmacy and Pharmaceutical Sciences*, 6(1), 142-145.
- Qi, B., & Yao, R. (2007). L-Lactic acid production from *Lactobacillus casei* by Solid State Fermentation Using Rice Straw. *BioResources*, 2(3), 419-429.
- Rathi, S. R., Coughlin, E. B., Hsu, S. L., Golub, C. S., Ling, G. H., & Tzivanis, M. J. (2014). Maintaining Structural Stability of Poly (lactic acid): Effects of Multifunctional Epoxy Based Reactive Oligomers. *Polymers*, 6(4), 1232-1250.
- Ren, P.J. (2009). *Biodegradable Poly (lactic acid): Synthesis, Modification, Processing and Applications: Springer Science & Business Media*.
- Roda, A., De Faveri, D. M., Dordoni, R., & Lambri, M. (2014). Vinegar production from Pineapple Wastes–Preliminary Saccharification Trials. *Cemical Engineering*, 37, 607-612.
- Rudeekit, Y., Numnoi, J., Tajan, M., Chaiwutthinan, P., & Leejarkpai, T. (2008). Determining Biodegradability of Polylactic acid Under Different Environments. *Journal of Metals, Materials and Minerals*, 18(2), 83-87.
- Rus, A. Z. M. (2010). *Polymers From Renewable Materials*. *Science Progress*, 93(3), 285-300.
- SabahelKhier, K. M., Hussain, A. S., & Ishag, K. (2010). Effect of Maturity Stage on Protein Fractionation, in Vitro Protein Digestibility and anti-Nutrition Factors in Pineapple (*Ananas Comosis*) Fruit Grown in Southern Sudan. *African Journal of Food Science*, 4(8), 550-552.
- Sairi, M., Yih, L. J., & Sarmidi, M. R. (2004, April). Chemical Composition and Sensory Analysis of Fresh Pineapple Juice and Deacidified Pineapple Juice using Electrodialysis. In *Regional symposium on Membrane science and technology* (pp. 21-25).
- Sánchez, A. C., & Collinson, S. R. (2011). The Selective Recycling of Mixed Plastic Waste of Polylactic acid and Polyethylene Terephthalate by Control of Process Conditions. *European Polymer Journal*, 47(10), 1970-1976.
- Saradhuldhat, P., & Paull, R. E. (2007). Pineapple Organic acid Metabolism and Accumulation During Fruit Development. *Scientia Horticulturae*, 112(3), 297-303.

- Sheeladevi, A., & Ramanathan, N. (2011). Lactic acid Production Using Lactic acid Bacteria Under Optimized Conditions. *International Journal of Pharmaceutical & Biological Archive*, 2(6), 1686-1691.
- Shi, G., Wang, G., Chen, X., & Li, C. (2013). Optically Pure L-Lactic acid Production Directly from Leftover Bits and Pieces of Potato Starch using an Amylolytic Pellet-form Complex *Rhizopus oryzae* ASC081. *Journal of Applied Science and Engineering*, 16(2), 205-210.
- Sichina, W. J., & Manager, M. (2009). *Characterization of Polymers Using TGA*. Perkin Elmer Instruments;PETech-78, 1–5.
- Sin, L. T., Rahmat, A. R., & Rahman, W. A. (2012). *Polylactic acid: PLA Biopolymer Technology and Applications*: William Andrew.
- Siti Roha, A., Zainal, S., Noriham, A., & Nadzirah, K. (2013). Determination of Sugar Content in Pineapple Waste Variety N36. *International Food Research Journal*, 20(4), 1941-1943.
- Silverajah, V. S., Ibrahim, N. A., Zainuddin, N., Yunus, W. M. Z. W., & Hassan, H. A. (2012). Mechanical, thermal and morphological properties of poly (lactic acid)/epoxidized palm olein blend. *Molecules*, 17(10), 11729-11747.
- Södergård, A., & Stolt, M. (2002). Properties of Lactic acid Based Polymers and their Correlation with Composition. *Progress in polymer science*, 27(6), 1123-1163.
- Somekawa, S., Masutani, K., Hsu, Y.-I., Mahara, A., Kimura, Y., & Yamaoka, T. (2014). Size-Controlled Nanomicelles of Poly (lactic acid)–Poly (Ethylene glycol) Copolymers with a Multiblock Configuration. *Polymers*, 7(6), 1177-1191.
- Sripaoraya, S., Marchant, R., Power, J., & Davey, M. (2001). Herbicide-Tolerant Transgenic Pineapple (*Ananas comosus*) Produced by Microprojectile Bombardment. *Annals of Botany*, 88(4), 597-603.
- Su, Wei-Fang. *Principles of Polymer Design and Synthesis*. Springer Berlin, 2013.
- Sun, X., Wang, Q., Zhao, W., Ma, H., & Sakata, K. (2006). Extraction and Purification of Lactic acid from Fermentation Broth by Esterification and Hydrolysis Method. *Separation and purification technology*, 49(1), 43-48.
- Survey, M. (2012). *Market Trends for Pineapple*. Tanzania Agriculture Productivity program, 9.

- Sutanto, A. (2012). Pineapple Liquid Waste as Nata de Pina Raw Material. *Makara of Technology Series*, 16(1).
- Subramanian, M. R., Talluri, S., & Christopher, L. P. (2015). Production of lactic acid using a new homofermentative *Enterococcus faecalis* isolate. *Microbial biotechnology*, 8 (2), 221-229.
- Trontel, A., Batušić, A., Gusić, I., Slavica, A., Šantek, B., & Novak, S. (2011). Production of D-and L-Lactic acid by Mono-and Mixed Cultures of *Lactobacillus* sp. *Food technology and biotechnology*, 49(1), 75-82.
- Ueno, T., Ozawa, Y., Ishikawa, M., Nakanishi, K. and Kimura, T. (2003). Lactic acid Production Using Two Food Processing Wastes, Canned Pineapple Syrup and Grape Invertase, as Substrate and Enzyme. *Biotechnol. Lett.*, 25, 573-577.
- Upadhyay, A., Lama, J. P., & Tawata, S. (2013). Utilization of Pineapple Waste: a Review. *Journal of Food Science and Technology Nepal*, 6, 10-18.
- Vaidya, A., Pandey, R., Mudliar, S., Kumar, M. S., Chakrabarti, T., & Devotta, S. (2005). Production and Recovery of Lactic acid for Polylactide - an Overview. *Critical reviews in environmental science and technology*, 35(5), 429-467.
- Vandanjon, L., Cros, S., Jaouen, P., Quéneur, F., & Bourseau, P. (2002). Recovery by Nanofiltration and Reverse Osmosis of Marine Flavours from Seafood Cooking Waters. *Desalination*, 144(1), 379-385.
- Vijayakumar, J., Aravindan, R., & Viruthagiri, T. (2008). Recent Trends in the Production, Purification and Application of Lactic acid. *Chemical and biochemical engineering quarterly*, 22(2), 245-264.
- Wasewar, K. L. (2005). Separation of Lactic acid: Recent Advances. *Chemical and biochemical engineering quarterly*, 19(2), 159-172.
- Wee, Y.-J., Kim, J.-N., & Ryu, H.-W. (2006). Biotechnological Production of Lactic acid and its Recent Applications. *Food technology and biotechnology*, 44(2), 163-172.
- Woo, S. I., Kim, B. O., Jun, H. S., & Chang, H. N. (1995). Polymerization of Aqueous Lactic acid to Prepare High Molecular Weight Poly (lactic acid) by Chain-extending with Hexamethylene Diisocyanate. *Polymer bulletin*, 35(4), 415-421.



- Xiao, L., Wang, B., Yang, G., & Gauthier, M. (2006). *Poly ( Lactic Acid ) -Based Biomaterials : Synthesis , Modification and Applications*.
- Yagi, H., Ninomiya, F., Funabashi, M., & Kunioka, M. (2009). Anaerobic Biodegradation Tests of Poly (lactic acid) Under Mesophilic and Thermophilic Conditions using Anew evaluation System for Methane Fermentation in Anaerobic Sludge. *International journal of molecular sciences*, 10(9), 3824-3835.
- Yang, T. H., Kim, T. W., Kang, H. O., Lee, S. H., Lee, E. J., Lim, S. C., Lee, S. Y. (2010). Biosynthesis of Polylactic acid and its Copolymers Using Evolved Propionate CoA Transferase and PHA Synthase. *Biotechnology and Bioengineering*, 105(1), 150-160.
- Yoo, D. K., Kim, D., & Lee, D. S. (2005). Reaction Kinetics for the Synthesis of Oligomeric Poly (lactic acid). *Macromolecular Research*, 13(1), 68-72.
- Yuris, A., & Siow, L.-F. (2014). A comparative Study of the Antioxidant Properties of Three Pineapple (*Ananas comosus L.*) Varieties. *Journal of Food Studies*, 3(1), 40-56.
- Y. Zhou, J.M. Dom ínguez, N. Cao, J. Du, G.T. Tsao, Optimization of L-lactic acid production from glucose by *Rhizopus oryzae* ATCC 52311, *Appl. Biochem. Biotechnol.* 78 (1999) 401–407.
- Zhang, J., Krishnamachari, P., Lou, J., & Shahbazi, A. (2009). Synthesis of poly (L (+) lactic acid) by polycondensation method in solution. Paper presented at the Proceedings of the 2007 *National Conference on Environmental Science and Technology* (pp. 3-8). *Springer New York*.
- Zhang, S., Feng, X., Zhu, S., Huan, Q., Han, K., Ma, Y., & Yu, M. (2013). Novel Toughening Mechanism for PolyLactic acid (PLA)/Starch Blends with Layer-Like Microstructure Via Pressure-Induced Flow (PIF) Processing. *Materials Letters*, 98, 238-241.
- Zhang, W.-x., & Wang, Y.-z. (2008). Synthesis and Properties of High Molecular Weight Poly (lactic acid) and its Resultant Fibers. *Chinese Journal of Polymer Science*, 26(4), 425-432.